

## **FEATURES**

- 865 866.9 MHz Radio
- Compact Design
- Easy Carrying
- Rain Resistant
- Crisp Voice
- Built in CTCSS / DCS
- VOX Function
- PC Programmable
- Power 1W
- Low Battery Alert

## **APPLICATION AREAS**

- Malls & Warehouses
- Hotels
- Hospitals
- Recreation and Leisure Centres
- Construction Sites
- Security Agencies
- Factories
- Emergency Signaling
- RWAs
- Sports Centre and Stadiums
- Schools and Colleges
- Farms
- Event Organisers
- Power Generation Companies



## **SPECIFICATIONS**

General	Transmit	Receive
Temperature Range: -10°C +60°C	Power output (at the input of Antenna): 1W	Sensitivity: 0.2uv for 5 db S/N
16 Stored Channels	Frequency Modulate (FM)	Squelch Sensitivity: <0.13uv
Antenna impedance 50 Ohm Antenna 5cm Gain 2.15 db Antenna 16.5 cm Gain 3 db	Max Frequency Offset: ≤ 5 kHz (Wide Band)	Receive Current: ≤ 150 mA
Weight - About 220 g	Distortion of Audio Frequency: ≤ 3%	Frequency Stability: ± 5 ppm
Battery: 2000 mAH Li-ion	Frequency Stability: ± 5 ppm Bandwidth of Emission: 12.5 K/ 25 K	Spurious Response: 57 db De-emphasis: ± 3 db Selectivity: 0.2uv for 5 db S/N

LICENSE FREE AS PER GOVT. ORDER GSR 564 (E) DATED 30th July 2008



## **AE Telelink Systems Ltd.**

Regd. Off.: 106, Rakeshdeep, Gulmohar Enclave Commercial Complex, New Delhi - 110049 (INDIA)
Tel: +91 - 11 - 41643059 Fax: +91 - 11 - 41841516 E-mail:catchall@aetelelink.com Website: www.aetelelink.com
Mkt. Off.: 1005, Ansal Tower-38, 10th Floor, Nehru Place, New Delhi - 110019 (INDIA) Tel: +91 - 11 - 41003644, 8010403042